

MATERIAL SAFETY DATA SHEET

Miller Auto Parts & Supply Company Inc.
10151 Fairgrounds Road
Huntingdon, PA16652
Phone: 814-643-4763
Emergency: 800-424-9300

Date Prepared: April 28, 2008
Prepared By: Technical Services
Date of Review/Update:

SECTION 1 - PRODUCT IDENTIFICATION

Item Number: 2075
Product Name: Final Touch

SECTION 2 - HAZARDOUS INGREDIENTS

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
2-Butoxyethanol	111-76-2	1-5	50ppm	25ppm

Listed as IARC, NTP, or OSHA Carcinogen:

HMIS Rating:

Health - 2 Fire - 0 Reactivity - 0 Personal Protection - C
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

SECTION 3 - PHYSICAL CHARACTERISTICS

Boiling Point: 212° F	Vapor Pressure (mmHg @ 68F):	N/A
Vapor Density: N/A	Solubility in Water:	Complete
Specific Gravity: 1.01 ± 0.02	Melting Points:	N/A
% Volatile: 80.0 - 82.0	pH:	5-6
Appearance/Odor: Violet Liquid, fruity odor		

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point / Method: N/A
Flammable Limits: N/A LEL: N/A UEL: N/A
Extinguishing Media: N/A
Special Fire Fighting Procedures: N/A
Unusual Fire and Explosion Hazards: N/A

SECTION 5 - HEALTH HAZARD DATA

Signs and Symptoms of Exposure:

Eye: Prolonged contact can cause irritation, redness, tearing, blurred vision.

Ingestion: Harmful or fatal if swallowed.

Skin: Mild Irritation possible

Breathing: Irritation to the respiratory system, nausea, headache.

Medical Conditions Aggravated by Exposure: Irritation to the eyes, skin and respiratory system.

Emergency & First Aid Procedures:

Eyes: Flush eyes with water for 15 minutes, get medical attention.

Ingestion: DO NOT induce vomiting. Drink plenty of water and seek medical attention.

Skin: Wash affected area with soap and water, if skin is damaged, seek medical attention.

Breathing: Remove individual to fresh air and seek medical attention.

SECTION 6 - REACTIVITY DATA

Stability: Stable.

Hazardous Polymerization: Will not occur.

Materials to Avoid: Oxidizing agents.

Conditions to Avoid: Mineral acids, oxidizing agents.

THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE.
ANY USE OF THIS PRODUCT THAT IS NOT IN CONFORMANCE WITH THIS MSDS IS THE SOLE RESPONSIBILITY OF THE USER.
2075 / Book 14.27

Hazardous Decomposition Products: N/A

SECTION 7 - SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled or Leaked: Pick up excess with a wet/dry vac. Rinse with water and allow to dry.

Waste Disposal: Dispose of in accordance with federal, state and local regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Ventilation: Use with adequate ventilation.

Respirator Protection: If required, a properly fitted NIOSH/MSHA approved respirator rated for hazardous ingredients found in section 2.

Skin Protection: Wear approved Nitrile gloves.

Eye Protection: Safety glasses with side shields.

Precautions to be taken in Handling and Storage: Wear proper gloves, glasses and safety shoes.

Special Storage Requirements: Keep in a dry environment.

SECTION 9 - REGULATORY INFORMATION

D.O.T. REQUIREMENTS (49CFR 172.101): Cleaning Compound NA1760 PG111

RQ (Reportable Quantity) 49 CFR 172.101:

TSCA (Toxic Substance Control Act) Status:

CERCLA RQ-40CFR 302.4:

SARA 302 COMPONENTS – 40CFR 355 Appendix A:

SECTION 311/312 HAZARD CLASS – 40CFR 370.2:

Immediate (X) Reactive () Delayed (X) Fire () Sudden release of pressure ()

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)

Ingredient	Max. % By Wt.	LD50	LC50
2-Butoxy Ethanol	1-5	50ppm	25ppm