

MATERIAL SAFETY DATA SHEET

Miller Auto Parts & Supply Company Inc.
10151 Fairgrounds Road
Huntingdon, PA 16652
Telephone: 800-424-9300
Emergency Telephone: 800-424-9300

Date Prepared: June 23, 2008
Prepared By: TECHNICAL SERVICES
Date Updated:

SECTION 1 - PRODUCT IDENTIFICATION

Item Number: 2125
Product Name: PEARL GLOSS RUBBER, VINYL & LEATHER DRESSING

SECTION 2 - HAZARDOUS INGREDIENTS

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>MAX %</u>	<u>OSHA PEL</u>	<u>ACGHI TLV</u>
OCTYLPHENOXYPOLYETHOXYETHANOL	9036-19-5	<2	N/A	N/A
ETHOXYLATED NONYLPHENOL	9016-45-9	<2	N/A	N/A
TRIETHYL-4-NONYLOXYPOLY ETHYLENE ETHANOL	60828-78-6	<2	N/A	N/A

Listed as IARC, NTP, or OSHA Carcinogen: None

HMIS Rating:

Health- 1 Fire- 0 Reactivity- 0 Personal Protection- C
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

SECTION 3 - PHYSICAL CHARACTERISTICS

Boiling Point:	212F	Vapor Pressure (mmHg @ 68F):	N/A
Vapor Density:	N/A	Solubility in Water:	SOLUBLE
Specific Gravity:	0.99 +/- 0.05	Melting Points:	N/A
% Volatile:	77 +/- 2	pH:	7.0 +/- 0.5
Appearance/Odor:	WHITE LIQUID, JASMINE SCENT		

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point / Method: None to Boil /
Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: N/A.
Special Fire Fighting Procedures: N/A
Unusual Fire and Explosion Hazards: None known

SECTION 5 - HEALTH HAZARD DATA

Signs and Symptoms of Exposure: Eye: May cause irritation, redness, tearing and blurred vision. Ingestion: Gastrointestinal Irritation. Skin: Dryness, mild irritation. Inhalation: Irritation of respiratory system, headache, fatigue.

Medical Conditions Aggravated by Exposure: Dermatitis.

Emergency & First Aid Procedures:

Skin: Wash affected area with soap and water. Remove contaminated clothing and launder before reuse.

Eyes: Flush with large amounts of water for 15 minutes. Consult a physician.

Ingestion: Do Not Induce Vomiting. Get medical attention.

Breathing: Remove to fresh air.

SECTION 6 - REACTIVITY DATA

THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE.
ANY USE OF THIS PRODUCT THAT IS NOT IN CONFORMANCE WITH THIS MSDS IS THE SOLE RESPONSIBILITY OF THE USER.
2125/BOOK 14.27

Stability: Stable
 Hazardous Polymerization: Will not occur
 Hazardous Decomposition Products: Various hydrocarbons of incomplete combustion.

Materials to Avoid: Strong Oxidizers
 Conditions to Avoid: Strong Oxidizers

SECTION 7 - SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled or Leaked: Ventilate and remove with inert absorbent.
 Waste Disposal: Dispose of in accordance with federal, state and local regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Ventilation: Use only with adequate ventilation. Avoid breathing of vapor or mist. Local exhaust preferred.
 Respirator Protection: Properly fitted NIOSH/MSHA approved respirator for ingredients found in section 2 if TLV is exceeded.
 Skin Protection: Gloves rated for protection for ingredients found in section 2
 Eye Protection: Safety glasses with side shields or chemical goggles.
 Precautions to be taken in Handling and Storage: Keep away from heat, sparks or other ignition sources.
 Special Storage Requirements:

SECTION 9 - REGULATORY INFORMATION

D.O.T. REQUIREMENTS (49CFR 172.101): None

SECTION 311/312 HAZARD CLASS - 40CFR 370.2

Immediate	(X)	Reactive	()
Delayed	(X)	Sudden Release of Pressure	()
Fire	()		

RQ (Reportable Quantity) 49 CFR 172.101
 None

TSCA (Toxic Substances Control Act) Status
 The intentional ingredients of this product are listed.

CERCLA RQ 40CFR 302.4
 None

SARA 302 Components 40 CFR 355 Appendix A
 None

SECTION 311/312 HAZARD CLASS 40CFR 370.2

Immediate () Delayed () Fire () Reactive () Sudden Release of Pressure ()

SARA 313 COMPONENTS
 None

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)

Ingredient	Max. % By Wt.	LD50	LC50
OCTYLPHENOXPOLYETHOXYETHANOL	<2	N/A	N/A
ETHOXYLATED NONYLPHENOL	<2	N/A	N/A
TRIETHYL-4-NONYLOXPOLY ETHYLENE ETHANOL	<2	N/A	N/A