

# MATERIAL SAFETY DATA SHEET

Miller Auto Parts & Supply Company Inc.  
10151 Fairgrounds Road  
Huntingdon, PA16652  
Phone: 814-643-4763  
Emergency: 800-424-9300

Date Prepared: October 1, 2007  
Prepared By: Technical Services  
Date of Review/Update:

## SECTION 1 - PRODUCT IDENTIFICATION

Item Number: 1857  
Product Name: Super Shine All Purpose Leather & Vinyl Dressing

## SECTION 2 - HAZARDOUS INGREDIENTS

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGHI TLV</u>
PETROLEUM DISTILLATE	8052-41-3	80 - 82	N/A	N/A
DIMETHYLPOLYSILOXANE	63148-62-9	20 - 25	N/A	N/A

Listed as IARC, NTP, or OSHA Carcinogen:

HMIS Rating:

Health - 1 Fire - 2                      Reactivity - 0                      Personal Protection - C  
0=Insignificant   1 = Slight   2 = Moderate   3 = High   4 = Extreme

## SECTION 3 - PHYSICAL CHARACTERISTICS

Boiling Point: N/A	Vapor Pressure (mmHg @ 68F): N/A
Vapor Density: N/A	Solubility in Water: Not soluble
Specific Gravity: 0.79 ± 0.05	Melting Points: N/A
% Volatile: 80.0 ± 0.2	pH: N/A
Appearance/Odor: Blue - Vanilla	

## SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point / Method: 115°F / TCC

Flammable Limits: LEL: 0.7 UEL: 5.0

Extinguishing Media: Use dry foam.

Special Fire Fighting Procedures: Containers can build up pressure if exposed to fire. Cool fire exposed containers with water fog.

Unusual Fire and Explosion Hazards: Vapors are heavier than air and can collect in low areas.

## SECTION 5 - HEALTH HAZARD DATA

Signs and Symptoms of Exposure:

Eye: Will cause irritation, redness, tearing and blurred vision.

Ingestion: Harmful or fatal if swallowed. May cause nausea, dizziness, confusion.

Skin: Prolonged contact will cause irritation or dermatitis.

Breathing: May cause dizziness.

Medical Conditions Aggravated by Exposure: None known

Emergency & First Aid Procedures:

Eyes: Flush with water or 15 minutes, seek medical attention.

Ingestion: DO NOT induce vomiting. Only give conscious victim two glasses of water and seek medical attention.

Skin: Wash with soap and water, If irritation persists, seek medical attention.

Breathing: Remove victim to fresh air.

## SECTION 6 - REACTIVITY DATA

THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE.

ANY USE OF THIS PRODUCT THAT IS NOT IN CONFORMANCE WITH THIS MSDS IS THE SOLE RESPONSIBILITY OF THE USER.

Stability: Stable.  
Hazardous Polymerization: Cannot occur.  
Hazardous Decomposition Products: Carbon Monoxide and Carbon Dioxide.

Materials to Avoid: Strong oxidizing agents.  
Conditions to Avoid: Excessive heat and open flame.

### **SECTION 7 - SPILL OR LEAK PROCEDURES**

**Steps to be taken if Material is Spilled or Leaked:** Notify safety personal, evacuate all unnecessary personal. Provide adequate ventilation. Clean up personal should wear protective equipment. Clean up spill with inert absorbent, place in recovery drum for proper disposal.  
**Waste Disposal:** Dispose of in accordance with federal, state and local regulations.

### **SECTION 8 - SPECIAL PROTECTION INFORMATION**

Ventilation: Strong ventilation or local exhaust.  
Respirator Protection: Organic vapor air purifying respirator.  
Skin Protection: Chemical resistant gloves such as nitrile.  
Eye Protection: Chemical splash goggles with side shields.  
Precautions to be taken in Handling and Storage: Wash thoroughly after using. DO NOT use near open flame.  
Special Storage Requirements: Store in dry area away from excessive heat.

### **SECTION 9 - REGULATORY INFORMATION**

**D.O.T. REQUIREMENTS (49CFR 172.101):** Not regulated when shipped in quantities less than 119 gallons. If more than 119gallons, consult proper shipping description 49CFR 173.120, Combustible Liquid UN1993 PGIII Petroleum Distillate.

**RQ (Reportable Quantity) 49 CFR 172.101:**

**TSCA (Toxic Substance Control Act) Status:**

**CERCLA RQ-40CFR 302.4:**

**SARA 302 COMPONENTS – 40CFR 355 Appendix A:**

**SECTION 311/312 HAZARD CLASS – 40CFR 370.2:**

Immediate ( X )    Reactive (   )    Delayed ( X )    Fire ( X )    Sudden release of pressure ( X )

#### **WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)**

Ingredient	Max. % By Wt.	LD50	LC50
PETROLEUM DISTILLATE	80 - 82	N/A	N/A
DIMETHYLPOLYSILOXANE	20 – 25	N/A	N/A