



MATERIAL SAFETY DATA SHEET

ECP Incorporated
11210 Katherine's Crossing, Suite 100
Woodridge, IL 60517
Telephone: 630-754-4200

Emergency Telephone: 800-424-9300
Date Prepared: February 4, 2002
Prepared By: Technical Services
Date Updated: December 2, 2008

SECTION 1 - PRODUCT IDENTIFICATION

Item Number: 1315
Product Name: Technician's Choice TEC565/32 Micro Glaze Swirl Remover

SECTION 2 - HAZARDOUS INGREDIENTS

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGHI TLV</u>
Petroleum Distillates	64742-48-9	5-15	100ppm	100ppm
Petroleum Distillates	64741-41-9	5-15	525ppm	100ppm

HMIS Rating: 0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme
Health- 1 Fire- 2 Reactivity- 0 Personal Protection- C

Listed as IARC, NTP, or OSHA Carcinogen: None

SECTION 3 - PHYSICAL CHARACTERISTICS

Boiling Point: 212f	Vapor Pressure (mmHg @ 68F): N/A
Vapor Density: N/A	Solubility in Water: Dispersible
Specific Gravity: 0.97+/-0.05	Melting Points: N/A
Appearance/Odor: Pink Creamy Liquid, Slight Strawberry Odor	% Volatile: 80

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point / Method: 114 F / TCC
Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: Use foam, dry chemicals or carbon dioxide.
Special Fire Fighting Procedures: Cool fire exposed containers with water fog.
Unusual Fire and Explosion Hazards: None known

SECTION 5 - HEALTH HAZARD DATA

Signs and Symptoms of Exposure: Eye: May cause irritation, redness, tearing and blurred vision. Ingestion: Harmful or fatal if swallowed. May cause nausea, dizziness, confusion, or unconsciousness. Skin: Prolonged or repeated contact may cause irritation or dermatitis.

Medical Conditions Aggravated by Exposure: None known.

Emergency & First Aid Procedures:

Skin: Wash off skin with water.

Eyes: In case of eye contact, flush eyes with water for 15 minutes. Contact a physician if irritation persists.

Ingestion: If ingested, DO NOT INDUCE VOMITING. Call a physician or poison control center.

Breathing: Remove to fresh air.

SECTION 6 - REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: N/A

Hazardous Decomposition Products: Carbon Monoxide and Carbon Dioxide

Materials to Avoid: None known

Conditions to Avoid: None known

SECTION 7 - SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled or Leaked: Contain and collect with absorbent.

Waste Disposal: Dispose of in accordance with federal, state and local regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Ventilation: Normal Air Circulation

Respirator Protection: NIOSH-Organic Vapor

Skin Protection: Nitrile /Vinyl Gloves

Eye Protection: Safety Glasses/Goggles

Precautions to be taken in Handling and Storage: None

Special Storage Requirements: Keep away from heat and fire. Do not allow to freeze.

SECTION 9 - REGULATORY INFORMATION

D.O.T. REQUIREMENTS (49CFR 172.101): Not regulated in quantities less than 119 gallons except when shipped by vessel or aircraft. If shipped by vessel or aircraft or in quantities more than 119 gallons then the following description applies:

FLAMMABLE LIQUID N.O.S. (PETROLEUM DISTILLATE) 3, UN1993, PGIII

SECTION 311/312 HAZARD CLASS - 40CFR 370.2

Immediate (X)

Delayed (X)

Fire (X)

Reactive ()

Sudden Release of Pressure ()

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)

Ingredient	Max. % By Wt.	LD50	LC50
Petroleum Distillate	20	Unknown	3400ppm/4hr inhl-rat

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH. HOWEVER, NO WARRANTY, EXPRESSED OR IMPLIED IS MADE.