



# MATERIAL SAFETY DATA SHEET

## Section 1: Chemical Product and Company Identification

Product Name: 2164  
Product Code: TEC 499 Green Sheen  
Product Class: Automotive Tire Dressing  
Manufacturer/Supplier: ECP Incorporated  
11210 Katherine's Crossing, Suite 100  
Woodridge, IL 60517  
Telephone: 630-754-4200  
Emergency Telephone: CHEMTREC 800-424-9300

Date Prepared: October 7, 2008  
Date of Review/Update:

<b>HMS Rating:</b>	Health-	1
	Fire-	0
	Reactivity-	0
	Personal Protection-	C
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme		

## Section 2:- Hazardous Ingredients

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% Range</u>	<u>OSHA PEL</u>	<u>ACGHI TLV</u>
Exthoxylated Nonylphenol	90146-45-9	<4%	N/A	N/A
Listed as IARC, NTP, or OSHA Carcinogen: None				

## Section 3: Hazard Identification

Signs and Symptoms of Exposure:

Eye: May cause irritation, redness, tearing and blurred vision.  
Ingestion: Gastrointestinal irritation  
Skin: Dryness, mild irritation  
Inhalation: Irritation of respiratory system, headache, fatigue.  
Medical Conditions Aggravated by Exposure: Dermatitis

## Section 4: First Aid Measures

Eye Contact: Flush with large amounts of water for 15 minutes. Consult a physician.  
Ingestion: Do not induce vomiting. Get medical attention.  
Skin Contact: Wash affected area with soap and water. Remove contaminated clothing and launder before reuse.  
Inhalation: Remove to fresh air.

## Section 5: Fire-Fighting Measures

Fire and Explosive Properties: None known  
Flash Point: None to boil  
Flammable Limits: LEL: N/A UEL: N/A  
Extinguishing Media: N/A  
Protective Equipment: N/A

## Section 6: Accidental Release Measures

Steps to be taken if Material is Spilled or Leaked: Ventilate and remove with inert absorbent.  
Waste disposal: Dispose of in accordance with federal, state and local regulations.

## Section 7: Handling and Storage

Precautions to be taken in Handling and Storage: Store in a cool dry place.

## Section 8: Exposure Controls and Personal Protection

Ventilation: Use only with adequate ventilation. Avoid breathing of vapor or mist. Local exhaust preferred  
Respirator Protection: Properly fitted NIOSH/MSHS approved respirator for ingredients found in section 2 if TLV is exceeded.  
Skin Protection: Gloves rated for protection for ingredients found in section 2  
Eye Protection: Safety glasses with side shields or chemical goggles.

The information given herein is given in good faith. However, no warranty expressed or implied is made. Any use of this product that is not in conformance with this MSDS is the sole responsibility of the user. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.

**Section 9: Physical and Chemical Properties**

Boiling Point: 212F  
Vapor Density: N/A  
Specific Gravity: 1.00-1.05  
% Volatile: 80 ±2  
Appearance/Odor: Green Liquid, Watermelon Fragrance

Vapor Pressure (mmHg @ 68°F): N/A  
Solubility in Water: Complete  
Melting Point: N/A  
pH: N/A

**Section 10: Stability and Reactivity**

Stability: Stable  
Hazardous Polymerization: Will not occur  
Hazardous Decomposition Products: Various hydrocarbons of incomplete combustion.

Materials to Avoid: Strong oxidizers  
Conditions to Avoid: Strong oxidizers

**Section 11: Toxicology Information**

**Section 12: Ecological Information**

**Section 13: Disposal Considerations**

Waste Disposal: Dispose of in accordance with federal, state and local regulations.

**Section 14: Transport Information**

D.O.T. REQUIREMENTS (49CFR 172.101): Not a regulated product.

**Section 15: Regulatory Information**

RQ (REPORTABLE QUANTITY) 49CFR 172.101

<u>Component</u>	<u>RQ (lb.)</u>	<u>For This Product</u>
N/A		

TSCA (Toxic Substances Control Act) Status  
The intentional ingredients of this product are listed.

CERCLA RQ - 40CFR 302.4  
N/A

SARA 302 COMPONENTS - 40CFR 355 Appendix A  
N/A

SECTION 311/312 HAZARD CLASS - 40CFR 370.2		
Immediate	( )	Reactive ( )
Delayed	( )	Sudden Release of Pressure ( )
Fire	( )	

SARA 313 COMPONENTS - 40CFR 372.65

WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)			
Ingredient	Max. % By Wt.	LD50	LC50

CALIFORNIA PROPOSITION 65

The information given herein is given in good faith. However, no warranty expressed or implied is made. Any use of this product that is not in conformance with this MSDS is the sole responsibility of the user. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.