

# MATERIAL SAFETY DATA SHEET

ECP Incorporated  
4700 South Central Avenue  
Chicago, IL. 60638  
TELEPHONE 708-496-7350  
EMERGENCY 800-424-9300

HMIS HAZARD RATING	
HEALTH	1
FIRE	0
REACTIVITY	0
PERSONAL PROTECTION	C

DATE OF PREPARATION  
21 JANUARY 2002  
BY TECHNICAL SERVICES

DATE OF REVIEW/UPDATE  
JUNE 15, 2006

## SECTION 1 - PRODUCT IDENTIFICATION

ITEM NUMBER

**5596**

ITEM DESCRIPTION

**TEC432 CLEAR DRESS**

PRODUCT NAME

**TECHNICIAN'S CHOICE TEC432 CLEAR DRESSING**

PRODUCT CLASS

Automotive rubber dressing

## SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENT CAS NUMBER	MAX. % BY WT.	TLV <sup>1</sup>	PEL <sup>2</sup>
--------------------------	------------------	------------------	------------------

NONE

Listed as IARC, NTP, or OSHA Carcinogen: None

## SECTION 3 - PHYSICAL CHARACTERISTICS

BOILING POINT:	212F
VAPOR PRESSURE(mmHg @ 68F)	UNKNOWN
VAPOR DENSITY(AIR=1)	UNKNOWN
SOLUBILITY IN WATER:	COMPLETE
SPECIFIC GRAVITY:	1.13+/-0.05
% VOLATILE (VOLUME)	43+/-2
MELTING POINT:	NOT APPLICABLE
EVAPORATION RATE(WATER=1)	UNKNOWN
APPEARANCE AND ODOR:	WATER WHITE LIQUID, BLAND ODOR

## SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT / METHOD:** NONE TO 212F / COC  
**FLAMMABLE LIMITS:** LEL: Unknown UEL: Unknown  
**EXTINGUISHING MEDIA:**  
Water fog, dry chemicals or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES:

Full protective equipment including self contained breathing apparatus for confined areas.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Water or foam may cause frothing. Use caution when directing water stream at frothing areas.

SECTION 5 - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

EYE: Irritation of eyes.
SKIN: Dryness.
INHALATION: Irritation of respiratory system.
INGESTION: Gastrointestinal irritation.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

None known.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION Remove exposure. Restore breathing. Keep warm and quite.
SKIN Wash affected area with soap and water. Remove contaminated clothing and launder before reuse.
EYES Flush with water.
IF SWALLOWED Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Seek medical attention.

SECTION 6 - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY: Strong oxidizers
HAZARDOUS DECOMPOSITION PRODUCTS: Various hydrocarbons of incomplete combustion.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 7 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR LEAKED:

Remove all sources of ignition. Contain spill. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD:

Dispose of in accordance with federal, state and local regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION

VENTILATION:

Use only with adequate ventilation. Avoid breathing vapor or mist. Local exhaust preferred.

RESPIRATORY PROTECTION:

Properly fitted NIOSH/MSHA approved respirator for ingredients found in (SECTION 2) if TLV is exceeded.

SKIN PROTECTION:

Gloves rated for protection against ingredients in (SECTION 2).

**EYE PROTECTION:**

Safety glasses with side shields or chemical goggles.

=====  
SECTION 9 - PRECAUTIONARY INFORMATION  
-----

**PRECAUTIONS TO BE TAKEN IN STORING AND HANDLING:**

Contents may burn. Keep away from any heat or spark source. Do not smoke. Empty containers can contain explosive vapors. Never use a torch to cut or weld on or near container. Never wear oil soaked clothing. Launder or dry-clean before wearing. Discard oil soaked shoes. Affix proper warning labels on containers in accordance with 29CFR 1010.1200.

=====  
SECTION 10 - REGULATORY INFORMATION  
-----

**D.O.T. REQUIREMENTS (49CFR 172.101)**

Not regulated

**RQ (REPORTABLE QUANTITY) 49CFR 172.101**

COMPONENT RQ (lb.) FOR THIS PRODUCT  
-----

NONE

**TSCA (Toxic Substances Control Act) Status**

The intentional ingredients of this product are listed or are not required to be listed.

**CERCLA RQ - 40CFR 302.4**

COMPONENT RQ (lb.) FOR THIS PRODUCT  
-----

NONE

**SARA 302 COMPONENTS - 40CFR 355 Appendix A**

NONE

**SECTION 311/312 HAZARD CLASS - 40CFR 370.2**

Immediate (X) Reactive ( )  
Delayed ( ) Sudden Release of Pressure ( )  
Fire ( )

**SARA 313 COMPONENTS - 40CFR 372.65**

NONE

**WORKPLACE HAZARDOUS INFORMATION SYSTEM (WHMIS)**

INGREDIENT MAX. % LD50 LC50  
, BY WT.

NONE

=====  
The information contained herein is based on data we believe to be correct. Any use of the product that is not in conformance with this MSDS or which involves using the product in combination with any other product or any process is the responsibility of the user.

<sup>1</sup> ACGIH

<sup>2</sup> OSHA